A380 Cabin & Cargo Customisation



A380 Kabinentechnologie, Integration & Test
Hamburg, Dec. 14th, 2006




A380 Kabinentechnologie, Integration & Test Table of Contents

- A/C Development Core Processes
- V&V Process Definitions
- V&V Process General View
- Classical vs. A380 Advanced Test Approach
- A380 Cabin0
 - Scope
 - Purpose
 - Pictures
 - Composition of Systems
 - Assets
 - First Virtual Flight
- A380 Systems Architecture



A380 Kabinentechnologie, Integration & Test A/C Development Core Processes





A380 Kabinentechnologie, Integration & Test V&V Process - Definitions

Requirements Validation

The purpose of **Requirements Validation** is to ensure that the requirements for a product are sufficiently correct and complete to achieve safety and to satisfy the needs of the customer within program constraints (e.g. cost, schedule).

Design Verification

The aim of **Design Verification** is to provide evidence that the design is compliant with the requirements. This compliance evidence is presented during design reviews and it is a key input to decisions on the choice of design solution and whether to proceeded to the next stage of development.

Product Verification


▶ The aim of *Product Verification* is to ensure that the product meets the requirements

Product Validation

Product Validation activities aim to demonstrate that the product meets the implicit needs of the customer



A380 Kabinentechnologie, Integration & Test V&V Process General View





A380 Kabinentechnologie, Integration & Test Classical vs. Advanced Test Approach A380

Classical Test Approach

- System Tests
 - performed on System Integration Benches (SIB). Focused on inherent System Functions, I/O to other Systems simulated.
- Multi System Tests

involve two or more Systems realized on SIBs to a Multi-SIB. Focused on Interfaces and Integration Aspects.

Advanced Test Approach for A380

- Aircraft Level Integration Tests
 involve SIBs and Multi-SIBs mechanically, electrically and electronically linked to the Cabin Integration Test Rig (CITR).
 Focused on Interfaces and System Dependencies.
- Cabin Virtual Flights (CVF)


execute Flight-Test Scenarios involving all available Cabin Systems. Focused on overall Cabin Aspects e.g. Human Factors and Cabin Operation. For each A380 HoV a dedicated CVF is planned.


15.12.2006


A380 Kabinentechnologie, Integration & Test A380 Cabin0 Scope



A380 Cabin0 comprises of








... more than 50 engineers permanently deployed

... verification of about 250 Cabin & Cargo System Functions











Airbus A380 Cabin0 is the facilitator to enhance the Cabin Maturity prior to EIS.

A380 Kabinentechnologie, Integration & Test A380 Purpose of Cabin0


A380 Cabin0 because of:

to test inherent functions and interfacing functionality of Cabin Systems

- ... in a comprehensive scope from Sub-System, System to A/C Level
- ... to ensure the required and specified functionality
- ... to detect system misbehavior in the development process
- ... to support the Ground & Flight Tests
- ... to achieve the required Operational Reliability at EIS




A380 Kabinentechnologie, Integration & Test A380 Cabin0 – Half Cut Fuselage





A380 Kabinentechnologie, Integration & Test A380 Cabin0 – Stairway view





A380 Kabinentechnologie, Integration & Test A380 Cabin0




A380 Kabinentechnologie, Integration & Test A380 Cabin0 Composition of Systems

- ✓ System
 Integration
 Bench (SIB)
- ✓ Multi System Integration Bench (Multi-SIB)
- ✓ Cabin Integration Test Rig (CITR)
- ✓ Cabin0 (CITR + SIB's)

Mechanical SIB

Electrical SIB

Cross-Function Tests





A380 Kabinentechnologie, Integration & Test A380 Cabin0 – Artic Cell

Outside

Cooling and heating of a complete 7-frame fuselage section similar to real flight and ground conditions

Temperature Envelope -30°C to +50°C

Cabin

Air conditioning close to reality with regard to

•Temperature 10°C to 50°C inside cabin


•Humidity 2g/kg to 18g/kg

•Air flow UD1440m³/h, MD1800m³/h

Air distribution Calibrated as in the aircraft

Complete furnishing of a fuselage section for realistic conditions of thermal comfort and airflow measurements

Permanent operation up to more than two weeks possible



The ARCTIC Cell is an important test facility to optimize comfort characteristics inside Airbus cabins.

A380 Kabinentechnologie, Integration & Test A380 Cabin0 Assets

Airbus View:


- ✓ Explore Integration and I/F Misalignments before starting Ground- and Flight-Tests
- ✓ Ground- and Flight-Tests campaigns essentially reduced thanks to prior Cabin0 tests
- ✓ Ground- and Flight-Test parameters specified more accurately based on extensive Cabin0 testing
- ✓ Re-play of Ground- and Flight-Test scenarios (cabin operation, failure case scenarios) in Cabin0 allow an efficient development of design solutions

Customer's View:

- ✓ Early familiarisation with new Cabin Systems (e.g. HMI, Maintenance)
- ✓ Beyond the EIS of the A380, the Cabin0 is the adequate mean for
 - solving In-Service Problems of the Cabin Systems prior to EIS
 - customisation purposes



A380 Kabinentechnologie, Integration & Test A380 Cabin0 First Virtual Flight





A380 Kabinentechnologie, Integration & Test A380 Cabin0 – APU (Auxiliary Power Unit)


Operation APU (Auxiliary Power Unit)

- APU air supply to the AGU/Mixing System Integration Bench
- Exchange of data signals via AFDX
- Electrical power generation for the industrial air heater
 within the APU-Bypass duct to simulate hot day and extreme hot day conditions
- APU pneumatical Power: 900 kW, electrical Power 300 kVA => total Power of appr. 1.2 MW

Operation Pneumatic-Power Test Bench

Execute of Request for Tests for,
 Bleed Air System, Engine Bleed Air System







A380 Kabinentechnologie, Integration & Test

A380 Cabin0 – Air Generation Unit Test Rig (AGU)

Major features:


- Air Generation Unit consists of 2 units (LH/RH)
- Compact design without any long ducting
- Cooling power appr. 450 kW
- Air Flow to Cabin: 2.5 2.7 kg/s
- Ram Flow 6.5 kg/s
- Air Exchange in the fuselage 20times/ hour
 (1 time/ 3 min)
- Examination of ice-formation in the Mixer Unit and in the AGU-Outlet-Duct (Icing Tests)
- AGU / Mixer System Integration
 - ➤ Temperature, pressure and air flow measurements at all representative positions (Mixing Chamber, Air distribution ducts, Recirc-System, AGU)







A380 Kabinentechnologie, Integration & Test A380 Cabin0 – Air Flow Distribution PST-System



A380 Kabinentechnologie, Integration & Test A380 Cabin0 – Supplemental Cooling System




Major features:

· LR/ SA

Air Chiller (Refrigerator) in each Galley


R134A cooling medium

- A380
 - Centralized Cooling Unit (CRU)
 - Cooling loop distributed towards galleys
 - heat dissipation routed overboard
 - Cooling power appr. 15kW (150 home refrigerators)



Galden Pump

A380 Kabinentechnologie, Integration & Test A380 Cabin0 – Water/ Waste Test Rig



- Vacuum toilet system incl. lower deck lavatories and options
- Potable water and waste water system incl. options (e.g. Shower, etc.)
- Disinfection and water treatment system
- Galley inserts



Logical Tests

- Usage
- Modes
- Safety

Electrical Tests

- Over/Undervoltage
- Inrush
- Transients



Physical Tests

- Flow
- Temperature
- Drainage




A380 Kabinentechnologie, Integration & Test

A380 Cabin0 - CIDS (Cabin Data Intercommunication System)

Main SIB features:

- Complete original A/C equipment from Directors via Data Busses to Decoder Encoder Units
- Partial original A/C equipment for flight attendant and passenger related units
- Representative customer configuration of SIB for each HoV possible
- System integration with all other original cabin systems possible (Cabin 0 concept)



END

Thank you for your attention!



© AIRBUS S.A.S. All rights reserved. Confidential and proprietary document.

This document and all information contained herein is the sole

This document and all information contained herein is the sole property of AIRBUS S.A.S.. No intellectual property rights are granted by the delivery of this document or the disclosure of its content. This document shall not be reproduced or disclosed to a third party without the express written consent of AIRBUS S.A.S. This document and its content shall not be used for any purpose other than that for which it is supplied.

The statements made herein do not constitute an offer. They are based on the mentioned assumptions and are expressed in good faith. Where the supporting grounds for these statements are not shown, AIRBUS S.A.S. will be pleased to explain the basis thereof.

AIRBUS, its logo, A300, A310, A318, A319, A320, A321, A330, A340, A350, A380, A400M are registered trademarks.



AN EADS COMPANY