

AIRCRAFT POLLUTANT EMISSIONS: FORMATION MECHANISM AND REDUCTION BY INLET AND FLAME TEMPERATURE OPTMIZATION.

Louis TSAGUE , Ph/D; National Advance school
of Engineering at University of YAOUDE I, BP
8390, [www//UY1.uninet.com](http://www.UY1.uninet.com); www.Polytechcm.org
Tel: 237-77-68-64-27 ;email : tontepeck@yahoo.fr,,

EWADE 2011 Workshop 27 May 2011, Naples, Italy

Abstract:

- ❖ Over the past years, many scientific have tried to reduce aircraft pollution.
 - ❖ The pollutants formation mechanism is explained from taxi to climb .
 - ❖ Then the relationship between pollutant emissions and inlet temperature and flame temperature is studied
 - ❖ The analysis has shown that there is a low emission zone according to inlet and flame temperature.
 - ❖ Combustion in the low emission zone can contribute to the reduction of pollutant emissions,
- Key Words:** Turbojet engine exhaust, EI_{NOx} , EI_{CO} , EI_{HC} , inlet temperature, flame temperature, low emission zone

Introduction

- ❖ Limitation regulation on aircraft exhaust pollutant emissions is more and more tightened.

- ❖ Aircraft exhaust pollutants formation mechanism is presented.

- ❖ Pollutant emissions according to the operational phase from taxi to climb are analyzed .

An attempt to find a suitable inlet temperature and flame temperature zone for low emission is done.


- ❖ With 556 turbojet engines data from a pretty piece of work done by Detlef Kretschmer on eleven gas turbine engines and ICAO data



EWADE 2011 Workshop 24–27 May 2011, Naples, Italy



EWADE 2011 Workshop 24–27 May 2011, Naples, Italy




Materials and Methods

- ❖ The approach uses 556 experimental data from a pretty piece of work realized by Kretchmer on eleven turbojet engines and ICAO data,
- ❖ Combustion of 11 fuel types in a wide range of inlet temperatures and pressures ranged from 290 to 851K and from 0.1 to 1.4MPa, respectively.
- ❖ The method used in this study is the least square method.

Turbojet engines pollutant formation mechanism

❖ Turbojet engines perform a kerosene combustion process in the combustion chamber according to the following chemical reaction:



NO_x Formation mechanism

❖ Thermal NO mechanism is the dominant source of NO_x in turbojet engine.

The maximum production of thermal NO_x is obtained at the equivalence ratio range of $\Phi=0.8\sim 1$.

❖ The prompt NO_x is formed in fuel rich and low temperature conditions, but it is not very significant compared to thermal NO_x.

❖ The four equations of the extended Zeldovich mechanism governing thermal NO_x formation

$$\frac{d \mathbf{EI}_{NOx}}{d\tau} = 1.5 \times 10^9 T_3^n \exp\left(\frac{-19500}{T_f}\right)$$

❖ CO Formation mechanism

- ❖ Carbon monoxide is formed at low temperatures due to lower reaction rates and less oxidation of CO to CO₂.
- ❖ Too much CO is always from rich condition where there is not enough oxygen to let the burn process finish getting to CO₂.
- ❖ The richer the conditions, the more CO one will have.
- ❖ The CO formation mechanism has two steps.
- ❖ The first step transforms the fuel into carbon monoxide and water and the last step oxidizes CO to CO₂.
- ❖ The combustion of JP-10 happens according to the following reactions:




UHC Formation mechanism

- ❖ Unburnt hydrocarbons (UHC) like carbon monoxide are associated to bad condition combustion .
- ❖ UHC is a result of bad combustion, raw fuel (HC) which goes into the combustion chamber, then comes out and is not burned up in the process.
- ❖ Emission of UHC is a result of local fuel-rich zones.
- ❖ The combustion process of jet-A fuel in a turbojet engine happens produce UHC according to the following equation

$$\frac{d\mathbf{C}_{12}H_{23}}{dt} = -10^{11.5} \left(\frac{P}{P_0} \right)^{-0.815} e^{\left(\frac{12200}{T} \right)} \left[\frac{9T}{10^4} - \frac{1}{2} \right] \sqrt{\mathbf{C}_{12}H_{23}} \mathbf{P}_2$$

Turbojet engines pollutants emission

- ❖ Carbon monoxide,
- ❖ Nitrogen oxides
- ❖ Unburnt hydrocarbon
- ❖ figure 1 shows the emissions of CFMI Turbojet engines EI_{CO} , EI_{NO_x} and EI_{HC} versus fuel flow at approach






Fig 2: GE Turbojet engines EI_{CO} , EI_{NOx} and EI_{HC} versus fuel flow at approach and taxi.

Reduction of turbojet engines emission by inlet and flame temperature optimization

- ❖ There is a strong relationship between nitrogen oxide emissions and inlet temperature
- ❖ Flame temperature also has relationship with nitrogen oxide production.

$$EI_{NOx} = A T_3^\alpha$$

$$EI_{NOx} = B T_f^\beta$$

- ❖ A, B, α and β are empirical constants.




Fig 3: E_{ICO} , E_{NOx} and E_{HC} from J79-56C are presented according to combustion chamber inlet temperature.

Figure 3 shows that there is a zone of temperature where the emissions of all the pollutant species are less than 10g/kg of fuel burnt. This zone is situated between 560 and 640 K.




Figure 4: J79-56C EI_{CO}, EI_{NOx} and EI_{HC} from J79-56C versus flame temperature.




Fig 5: EI_{CO} , EI_{NOx} and EI_{HC} versus inlet temperature from F101, J79-56A, J79-56C, P&W and T56 Allison




Fig 6: EICO, EINOx and EIHC versus flame temperature (F101, J79-56A, J79-56C, P&W and T56 Allison)

Methods to optimize the inlet and flame temperature

- ❖ The air can be preheated or premixed and controlled so that it enters the combustion chamber with a constant temperature of 600K.
- ❖ Poor combustion at low temperature could be the other way to reduce emissions .
- ❖ Suitable value of flame temperature for the lowest emission production is 2500 K.
- ❖ This flame temperature can be obtained from specific fuels .
- ❖ Water or steam injection used in grounded gas turbine engine to decrease flame temperature can reduce nitrogen oxides.
- ❖ This technology can not be used in aircraft turbojet engines.

Conclusion

- ❖ Nitrogen oxides emissions increase with the evolution of fuel flow and flame temperature.
- ❖ Carbon monoxide and unburned hydrocarbon decrease with fuel flow, inlet and flame temperature evolution.
- ❖ Nitrogen oxides emissions are higher than the CO and UHC emissions at take off and climb,.
- ❖ At approach and taxi, CO and UHC emissions are higher than NOx
- ❖ The lowest emission zone in which the control of inlet and flame temperature for turbojet engines emissions reduction has been defined.
- ❖ Turbojet engine emissions have to be taken into account since the beginning of aircraft design
- ❖ What about spacecraft pollutant emissions?



THANK YOU FOR
YOUR KIND
ATTENTION