Dieter Scholz

Calculating the Wing Lift Distribution with the Diederich Method in Microsoft Excel

Aim of this project is to provide the Diederich Method for calculating the lift distribution of a wing in a Microsoft Excel spreadsheet based on didactic considerations. The Diederich Method is described based on primary and secondary literature. Diagrams are digitized so that the method can run automatically. To optimize the lift distribution of the wing, the elliptical and triangular lift distribution as well as Mason's lift distribution are offered for comparison. A method for calculating the maximum lift coefficient of the wing is integrated into the Diederich Method. To do this, the maximum lift coefficients of the airfoils at the wing root and at the wing tip must be entered in the program. The calculation assumes a trapezoidal wing. Both wing sweep and linear wing twist can be taken into account. The aspect ratio must not assume values that are too small. Subsonic flow and unseparated flow are assumed. Since only the wing is described, all other influences such as from the fuselage or from the engines are not taken into account. The Excel workbook was created for teaching in aircraft preliminary design. At the moment, the Diederich Method is apparently nowhere offered as a spreadsheet. With this work, this gap can be closed.

This informative poster is based on a student project with the same title. Details here: <u>https://nbn-resolving.org/urn:nbn:de:gbv:18302-aero2023-04-13.012</u>

	A B	С	D	E	F G	ł	4 I		J	K	L	M	N	0	Р	Q	R	S
	Diederich's Method																	
2																		
3																		
4																		
5																		
6	Input																	
7					_					Lift	Distri	bution	along	a Wing	's Halfs	pan		
8	General Input					3,0												
9	Aspect ratio	A	10,0		-													
10	Taper ratio	λ	0,16	•														
11	Quarter chord sweep	Ø1.25	25	deg	1													
12	Machnumber	м	0,8	•	-	2,5												
13	Twist	51	-10,0	deg	-													
14	Wing lift coefficient	C.	1,367	•	J						-+++							
15						20 -												
10	Additional input		0.5		1	-,-												
10	Tiele elitede	с. ь	3,5	m	-													
19	Relative thickness at the root	(t/o)	24%	Km	્													
20	Belative thickness at the tin	(00)	12%		1	1,5 -									_			
21	Airfoil trailing edge angle at the root	(32.0	dea	Г						#	_						
22	Airfoil trailing edge angle at the tip	(() () () () () () () () () (15.0	dea	1													
23	Maximum section lift coefficient at the root	0	13		1												\sim	
24	Maximum section lift coefficient at the tip	0	17		1	1,0 -												
25	realized at the operation of the operati	V(,e.e.)			1													
26	Output																	
27																		
28	Maximum Lift Coefficient Calculated		Solver: zero		1	0,5 -												
29	min. [section max. lift of the airfoil minus required lift]		1,212E-04]						+++							
30	Diederich's Lift Distribution Compared	_	Solver: minimize	_														
31	Error to elliptical lift distribution	•	2,963E+00	•		0.0												
32	Error to Mason's lift distribution	•	2,642E+00			()	0,1	0,	2	0,3	0,	4	0,5	0,6	0,7	0,8	0,9 1
33	Error to triangular lift distribution		1,624E+01										η-	2y/b				

Figure 1: Screen shot of part of the display of the Excel workbook to calculate the lift distribution and the maximum lift coefficient of a wing with the Diederich Method.

This is an abstract answering the Call for Papers of the German Aerospace Conference 2024 for an informative poster at the conference.

Prof. Dr.-Ing. Dieter Scholz, MSME Hamburg University of Applied Sciences Department of Automotive and Aeronautical Engineering Aircraft Design and Systems Group (AERO) http://www.ProfScholz.de info@ProfScholz.de